



Beam IntelliDOCK for Iridium 9555

IRIDIUM NETWORK	9555 Handset Compressed Data Voice / Data Modulation	1616 - 1625 MHz 10 - 12 kbps 2.4 kbps
Power Specifications	Power input voltage AC Power Pack Power Consumption (AMPS) Stand-by* - inc handset Transmit - inc handset Sleep Mode	9-32V DC, 2A max 90-250V AC 50-60Hz, Output 12V 45W 45mA 0.5W 0.5A 6W 18mA 0.2W
Physical Specifications	Dimensions – mm Dimensions - inches Weight – kg Weight – lbs	IntelliDOCK Packed 200x75x65 325x140x88 7.9x3.0x2.7 7.2x5.1x1.0 0.32 1.3 0.7 2.86
Environment Specifications	Operating Range Storage Humidity	Degrees °C Degrees °F -30 to +70 -22 to +158 -40 to +85 -40 to +185 < 93% RH
LEDS / Buttons	Bluetooth Ringer Backlight Handset Release	Blue / Orange Red White LED Top of Cradle - No LED
Connectors / Interfaces	Iridium - Antenna 9 - 32VDC Privacy Handset Port Data Port Bluetooth Voice Only	Fixed Cable to SMA-Female Screw Connector Round 4 Way USB Mini Base of Dock Inbuilt
Kit Contents	Beam 9555DOCK Unit Ram-Mount Steel Mounting Bracket Interface & Power Cables User & Installation Manual	
Certifications	Iridium Electrical Safety EMC Compliance C Tick CE Compliance RoHS	

*Independent Aeronautical certification MUST be gained prior to installation.